



PGDQ8.MH12039

Marking and Labeling Systems Certified for Canada - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Marking and Labeling Systems Certified for Canada - Component

[See General Information for Marking and Labeling Systems Certified for Canada - Component](#)

CM ASSOCIATES, DIV OF CYPRESS MULTIGRAPHICS INC

MH12039

UNIT A

8500 W 185TH ST

TINLEY PARK, IL 60487 USA

Model No.	Application Surface	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Pressure-sensitive printed labels.					
A4 White (Type A)					
	Metals	60	X	-	-
	Plastic Group IV	60	X	-	-
CMA SYSTEM P1, CMA SYSTEM P1L (Type A)					
	Metals	100	X	X	O
	Electrostatic coated metal A	100	X	X	O
	Electrostatic coated metal B	100	X	X	-
	Electrostatic coated metal C	100	X	X	O
	Electrostatic coated metal D	100	X	X	-
	Plastic Group I	80	X	X	-
	Plastic Group II	80	X	X	-
	Plastic Group III	80	X	X	-
	Plastic Group IV	80	X	X	O
	Plastic Group V	80	X	X	-
	Plastic Group VI	80	X	X	-
	Plastic Group VII	80	X	X	-
	Plastic Group VIII	80	X	X	-
CMA System P1-HS (Type A)					
	Metals	100	X	X	-
	Electrostatic coated metal A	100	X	X	-
	Electrostatic coated metal B	100	X	X	-
	Electrostatic coated metal C	100	X	X	-
	Electrostatic coated metal D	100	X	X	-

	Plastic Group I	80	X	X	-
	Plastic Group II	80	X	X	-
	Plastic Group III	80	X	X	-
	Plastic Group IV	80	X	X	-
	Plastic Group V	80	X	X	-
	Plastic Group VI	80	X	X	-
	Plastic Group VII	80	X	X	-
	Plastic Group VIII	80	X	X	-
CMA System P1L-HS (Type A)					
	Metals	100	X	X	-
	Electrostatic coated metal A	100	X	X	-
	Electrostatic coated metal B	100	X	X	-
	Electrostatic coated metal C	100	X	X	-
	Electrostatic coated metal D	100	X	X	-
	Plastic Group I	80	X	X	-
	Plastic Group II	80	X	X	-
	Plastic Group III	80	X	X	-
	Plastic Group IV	80	X	X	-
	Plastic Group V	80	X	X	-
	Plastic Group VI	80	X	X	-
	Plastic Group VII	80	X	X	-
	Plastic Group VIII	80	X	X	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

O - Occasional exposure to Lubricating Oil.

NOTE - (1) Additional characters may be added to the end of the designation after a forward slash, "/", indicating the type of release liner used unless a specific release liner is indicated. (2) Model designations may or may not include hyphens or spaces as part of the nomenclature.



Marking: Company name, model designation and the Recognized Component Mark for Canada, .

[Last Updated](#) on 2013-10-15

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online

Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".